



COVER

COVER



General tolerance
cross section

0 to 6	6 to 30
± 0.5	± 1.5

PRODUCT DESCRIPTION

- Plastic cover
- Colour: Transparent, Diffuse, White
- Material: PMMA
- Provides maximum lighting comfort for all applications
- No tools required for installing
- Radiation: 120°
- UV-resistant

TECHNICAL DATA

Dimensions L x W x H	2,000 ¹ x 20 x 10 mm
Coefficient of linear expansion	85 * 10 ⁻⁶ / K
Operating temperature	-30 ... +80 °C
Storage temperature ts	-30 ... +80 °C
¹ Tolerance length:	- 0 mm / + 20 mm

RoHS

ORDERING DATA - COVER

Colour	Transmission	Weight	Type	Length	Art. Nr.
White	75 %	0,17kg	LED Z220 Cover white	2m	24138742
Diffuse	92 %	0,17kg	LED Z221 Cover frosted	2m	24138743
Transparent	92 %	0,17kg	LED Z222 Cover clear	2m	24138738

Packaging: 10 pieces/carton, 250 pieces/pallet

Mounting notes

- The cover has to be snapped onto the profile.

STANDARDS

- EN 60598-1

The lens passed the heat filament test with 650°C as required in EN 60598-1