









DATASHEET







IP00	LEDtape 2700K CRI95 1000LM 10W 24V 5M G4
Code	W1004-927-5M-G4
	7506480
	3201174
	4127400
	7350102530329







IP68	LEDtape 2700K CRI95 1000LM 10W 24V IP68 5M G4
Code	W1004-927-IP68-5M-G4
	7506481
	3201175
	4127401
	7350102530336











IP00	LEDtape 3000K CRI95 1000LM 10W 24V 5M G4
Code	W1004-930-5M-G4
	7506482
	3201176
	4127402
	7350102530343



IP68	LEDtape 3000K CRI95 1000LM 10W 24V IP68 5M G4
Code	W1004-930-IP68-5M-G4
	7506483
	3201177
	4127403
	7350102530350



IP00	LEDtape 4000K CRI95 1000LM 10W 24V 5M G4
Code	W1004-940-5M-G4
	7506484
	3201178
	4127404
	7350102530367

IP68	LEDtape 4000K CRI95 1000LM 10W 24V IP68 5M G4
Code	W1004-940-IP68-5M-G4
	7506485
	3201179
	4127405
	7350102530374

HIGHLIGHTS

- Flexible LEDtape for professional lighting applications with high density and light output
- Colour temperature 2700K, 3000K and 4000K
- Ultra-high CRI>95
- Available in IP00 and IP68-version
- High efficiency >100 lm/W
- Best in class colour tolerance – MacAdam 3
- Possible to connect 10 meters in series ⑥
- Optimal for homogenous illumination at short distances
- 168 LEDs per meter
- High quality adhesive 3M-tape on backside for easy mounting on common surfaces
- Long lifetime: L70 = 50 000h ①
- Optimized for high resolution digital dimming 0.1-100% using Welight LED-driver W71XX-series.
- Can be made to order in any CCT between 2000-6500K. Contact us for more details.

Accessories

- Solder-free connectors and bridges (included)
- Aluminium profiles for linear and corner applications
- Wide variety of lenses and covers
15°/30°/60°/120°/Asymmetric/Batwing
- Fixed or adjustable mounting brackets
- Optimised drivers to fit every need and application

Technical Data

 pp. 2

Accessories

 pp. 5

Mounting Instructions

 pp. 7

TECHNICAL DATA

Packaging


Full carton	20 pcs
Weight per pc	IP00: 600 g IP68: 900 g
Box dimensions	250 x 250 x 30 mm

Electrical ①

Supply voltage (VDC)	24
DC Voltage Range ④⑥	22-26V @ L ≤5m 24-26V @ L ≤10m
Power (W) per m	10
Current (mA) per m	415
Supply Cable	L = 1 m (both ends) AWG20 UL standard BK (Black -) RD (Red +)

Dimensional ②

Length (L)	5 m
Max length in series ⑥	10 m
Min Bending Radius	IP00: 30 mm IP68: 50 mm
Width (W)	IP00: 10 mm IP68: 12 mm Incl. Endcap: 14 mm
Height	IP00: 1,4 mm IP68: 4,5 mm Incl. Endcap: 6,5 mm
Cutting length (C)	41,6 mm
Pitch distance (P)	6 mm



Temperature and Lifetime

Performance Temp Rating (Tp)	65 °C
Operating Temp Range (Ta) ⑤	-35/+50 °C
Max PCB Temp (Tc)	75 °C
Storage Temp	-35/+80 °C
L70F10 @Tp	50 000 h
L90F10 @Tp	35 000 h
Adhesive	3M VHB 5-year warranty
Warranty Period @Tp	5 years

Safety & Compliance

Constant Current IC	Yes, bipolar IC
Insulation Voltage	0,5kV DC 10mA 60sec
IEC Standards	IEC 62031 IEC 62471 IEC 62717 IEC 61000-4-2
ESD Class	1
Risk group (EN 62471:2008)	1
Classification acc. to IEC 62031	Class III
Energy Declaration (EEEL)	A+ 10 kWh / 1000h

Optical ①③

Luminous Flux (lm) per m	1000
Beam Angle	120
LED package	2835
LED quantity per m	168
MacAdam SDCM	≤3
CRI (R1-R8)	>95
CRI (R1-R14)	>95

Photometric Code (according to EN 62717)

White Tone	CCT	Photometric Code
Incandescent	2700 K	927 / 349
Warm	3000 K	930 / 349
Neutral	4000 K	940 / 349

① Tolerance range for electrical and optical data ±10%

② Tolerance range for dimensional data ±1%




③ All values for ta = 25 °C / tc = 65 °C

④ Measured at the beginning of the LEDtape. Exceeding the maximum operating voltage leads to an overload on the tape. This may result in a significant reduction in lifetime or even destruction of the tape.

⑤ Self-cooling at ta ≤ 35 °C

⑥ When connecting 10 meters in series, the supply voltage must be between 24-26V at the beginning of the tape. Lower voltage can cause a significant reduction in light output at the end of length.


Chromaticity coordinates and tolerances (according to CIE 1931)



The specified color coordinates are measured by a current impulse with nominal values of module after a settling time of 100 msec. The ambient temperature of the measurement is $t_a = 25\text{ }^{\circ}\text{C}$. The measurement tolerance of the color coordinates is ± 0.01 .

WIRING

The LEDtape is delivered with colour coded connection cable at each end, L = 1 m, 2 x 0,5 mm² (AWG20).
Do not connect more than 10 meters in series and make sure that the voltage is within the specified range at the beginning of the LEDtape.



DIGITAL DIMMABLE DRIVERS

Welight offers a range of suitable LED-drivers especially designed for high-end dimmable applications.



	Control Signal	Art. Code	Driver Type	Max length per driver
1	DALI-2	W7101	LEDdriver LCV 100W 24V 1-4CH DALI2 SR	10 m
2	KNX	W7102	LEDdriver LCV 100W 24V 1-4CH KNX SR	10 m
3	DMX	W7103	LEDdriver LCV 100W 24V 1-4CH DMX SR	10 m
4	one4all ①	28001920	LCA 35W 24V one4all SC PRE	3.5 m
5	one4all ①	28001921	LCA 60W 24V one4all SC PRE	6 m
6	one4all ①	28001922	LCA 100W 24V one4all SC PRE	10 m
7	one4all ①	28001923	LCA 150W 24V one4all SC PRE	15 m
4	bDW / Casambi	28002677	LC 35W 24V bDW SC PRE2	3.5 m
5	bDW / Casambi	28002674	LC 60W 24V bDW SC PRE2	6 m
6	bDW / Casambi	28002675	LC 100W 24V bDW SC PRE2	10 m
7	bDW / Casambi	28002678	LC 150W 24V bDW SC PRE2	15 m

① The driver can be controlled via DALI DT6, DSI, switchDIM, corridorFUNCTION and ready2mains.

CABLE & CONNECTION ACCESSORIES



1



2



3



4



5



6



7



8



9



10



11



12



13



14



15



16



17



18

Pic	Type	Art. Code	Description	Included	Suitable for LEDtape	
					IP00	IP68
1	LEDtape Connector Strip-Strip	W8434	Connect IP00 strips to each other	1 pc	✓	✗
2	LEDtape Connector Strip-Cable	W8435	Connect IP00 strip to a 2-wire cable (cable not included). Max cross section AWG20 (0,5mm²).	1 pc	✓	✗
3	LEDtape Connector Slim Strip-Strip	W8436	Connect IP00 strips to each other inside a confined space, e.g. a mounting profile (cable not included)	1 pc	✓	✗
4	LEDtape Connector Slim Strip-Cable	W8437	Connect IP00 strip to a 2-wire cable inside a confined space, e.g. a mounting profile (cable not included). Max cross section AWG20 (0,5mm²).	1 pc	✓	✗
5	LEDtape Connector IP Strip-Strip	W8438	Connect IP68 strips to each other ⚠	1 pc	✗	✓
6	LEDtape Connector IP Strip-Cable	W8439	Connect IP68 strip to a cable (20cm cable included) ⚠	1 pc	✗	✓
7	LEDtape Connector Strip-Corner-Strip	W8451	Connect IP00 strips in a 90° angle. Suitable for corners.	–	✓	✗
8	LEDaccessory Plug Connector 2P IP20 36V 9A	W8412-D2	Pluggable Cable Joint. Can act as both female and male by turning it upside down. Max cross section AWG20 (0,5mm²).	–	✓	✗
9	LEDaccessory T Splicer 2P IP20 300V 10A	W8412-T2	T Splicer. Can be used to split the supply cable in two directions. Max cross section AWG20 (0,5mm²).	–	✓	✗
10	LEDaccessory Connector IP68 kit F+M	W8411-A2	IP68 connector with lockable female and male plug incl. 30cm cable, white	–	✗	✓
11	LEDcable RKUB 2X0.5 AWG20 Rd/Bk 6m	W8417	Black/red connection cable, 6m reel. Indoor use only.	–	✓	✓
12	LEDcable RKUB 2X0.5 AWG20 W/W 6m	W8418	White connection cable, 6m reel. Indoor use only.	–	✓	✓
11	LEDcable RKUB 2X0.5 AWG20 Rd/Bk 100m	W8421	Black/red connection cable, 100m reel. Indoor use only.	–	✓	✓
12	LEDcable RKUB 2X0.5 AWG20 W/W 100m	W8422	White connection cable, 100m reel. Indoor use only.	–	✓	✓
13	LEDcable RKKB 2X1 Rd/Bk Yd 5,8mm Bk 100m	W8413	Black/red connection cable with UV-resistant insulation, 100m reel. Suitable for outdoor use. ⚠ Not compatible with quick connectors!	–	✓	✓
14	LEDtape 3M VHB Adhesive 10mm 33m reel	W8449	Additional adhesive for repairing or replacing the adhesive on the back of LEDtape IP00 and IP68. Pre-cut to fit PCB width 10mm. Reel length 33m.	–	✓	✓
15	LEDtape IP Endcap	W8432	Suitable for sealing the end of a cut LEDtape IP68. Use with W8433.	5 pcs	✗	✓
16	LEDtape Silicon Tube with tip	W8433	Suitable for sealing the end of a cut LEDtape IP68. Can be used together with W8432 for optimal protection.	1 pc	✗	✓
17	LEDtape IP Assembly Kit 10	W8901	Endcaps, Mounting Brackets & Silicon	–	✗	✓
18	LEDtape Mounting Clip	W8430	Mounting clip with single screw for IP00-rated LEDtape	10 pcs	✓	✗
18	LEDtape Mounting Clip IP68	W8431	Mounting clip with single screw for IP68-rated LEDtape	10 pcs	✗	✓



When properly applied the overall IP-rating of the solution will be IP67.

PROFILE SYSTEMS & LENSES

Start by selecting an aluminium **profile (A)** and a suitable **lens cover (B)** and then add optional **accessories (C)**.

(A)



1

2

3

Optional accessories

Pic	Type	Art. Code	L (mm)	W (mm)	H (mm)	W (mm) incl. lens cover	H (mm) incl. lens cover	Application	Lens Cover	End Cap	Fixed Mount	Adjustable Mount
1	Z200-2	24166148	2000	18	9	21	16	Corner	✓	✗	✗	✗
2	Z201-2	24166149	2000	18	9	21	16	Linear Slim	✓	✓	✓	✗
3	Z22W-2	24166150	2000	18	16	21	24	Linear	✓	✓	✓	✓

(B)



1

2

3

4

5

6

7

Profile

Pic	Type	Art. Code	L (mm)	Mounting Method	Typ. application	Z200-2	Z201-2	Z22W-2
1	15°	24166405	2000	Slide-on	Wall wash	✓	✓	✓
2	30°	24166409	2000	Slide-on	Wall wash	✓	✓	✓
3	60°	24166410	2000	Slide-on	Shelf/Cabinet	✓	✓	✓
3	90°	24166411	2000	Slide-on	Shelf/Cabinet	✓	✓	✓
4	30° x 60°	24166412	2020	Slide-on	Asymmetric	✓	✓	✓
5	Batwing	24166123	2000	Snap-on	Side-emitting	✗	✗	✓
6	120°	24138743	2000	Snap-on	Accent / Cove	✓	✓	✓
7	Opal	24138742	2000	Snap-on	Accent / Cove	✓	✓	✓

(C)



1

2

3

4

5

Profile

Pic	Type	Art. Code	Z200-2	Z201-2	Z22W-2
1	End cap Grey PMMA	24166334	✗	✓	✗
2	End Cap Aluminium	24139174	✗	✗	✓
2	End Cap Aluminium Cable Entry	24139173	✗	✗	✓
3	Mounting Bracket 0°	88166859	✗	✓	✓
4	Mounting Bracket 15°	88167372	✗	✓	✓
4	Mounting Bracket 30°	88167373	✗	✓	✓
4	Mounting Bracket 45°	88167374	✗	✓	✓
4	Mounting Bracket 60°	88167375	✗	✓	✓
5	Mounting Bracket Adjustable	24166024	✗	✗	✓


LEDtape Indoor Series IP00

INSTRUKTIONER
INSTRUCTIONS
ANLEITUNG
ISTRUZIONI
INSTRUCCIONES




INSTALLATION

1



Never bend the LEDtape at a radius smaller than 30 mm.

2




Assembly must not damage or destroy conducting paths on the PCB.

3

Perform the Pre-connection Checklist:


- ✓ Maximum length connected in series:
→ Datasheet | Wiring
- ✓ Polarity and Cable Colour Coding:
→ Datasheet | Wiring
- ✓ Maximum length per driver:
→ Datasheet | Digital Dimmable Drivers

4




The fixing/cooling surface must be properly cleaned to remove grease, dirt and silicon before application, e.g. using Isopropyl alcohol.

5



Remove the adhesive tape from the backside and fix the LEDtape on the cleaned fixing/cooling surface.


6



When fixing the LEDtape to a surface, apply an even but gentle pressure and try to avoid applying pressure directly on the LED itself (the maximum allowed pressure is 20 N/cm²).


After assembly always check that the entire length has attached properly to the surface and that there is no air pockets underneath.

7



If the total length is longer than 2 meters it is recommended to use the included screw mounting clips in addition to the adhesive tape.


8



Always use our approved drivers and controls to power the LEDtape. If the wrong type of driver is used the product warranty is void.


→  [Datasheet | Digital Dimmable Drivers](#)

9




The temperature on the surface of the LEDtape (tc) may under no circumstances be higher than 65 °C if the expected lifetime of the LEDtape is to be met.


CUT & SOLDER



The LEDtape is separable at the middle of every solder pad with the full function of each LED segment. It is only allowed to cut at the indicated cutting line.



Always cut the LEDtape in a straight line – 90° in relation to the PCB edges. Use Welight's official connection accessories to split, connect, and bridge the LEDtape.




If you need to solder the LEDtape, pre-tin the cables only. Soldering temperature max 300 °C for 4 seconds.

For details on how to solder an IP00 LEDtape, please watch this VIDEO TUTORIAL:




LEDtape Indoor Series IP00

KOPPLINGS
DON
CONNECTORS
VERBINDER
CONNETTORI
CONECTORES




STRIP TO CABLE

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the PCB.

3



Open the cap as much as possible and insert the LEDtape all the way to the back of the connector.

4




Use a pair of flat pliers to press down on each side of the cap until they lock in position. A "CLICK" can be heard when the pins are locked.

5



Insert the cable all the way to the back of the connector. Make sure you **match the POLARITY** of the LEDtape before locking the connector in place.


6



Use a pair of flat pliers to press down on each side of the cap until they lock in position. A "CLICK" can be heard when the pins are locked.


STRIP TO STRIP

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the PCB.

3




Open the cap as much as possible and insert the LED-strip all the way to the back of the connector.

4



Use a pair of flat pliers to press down on each side of the cap until they lock in position. A "CLICK" can be heard when the pins are locked.

5



Repeat steps 1-4 for the other connecting end of the LEDtape. Make sure you check that both ends are facing the **SAME POLARITY** before locking the last connector in place.


If you are in doubt, consider soldering your connection instead. There is no substitute for a permanent soldered connection.

VIDEO TUTORIAL:



Do NOT use Quick Connectors when...

- ✗ You need to connect a pre-soldered joint.




- ✗ Your LED strips might be subjected to movement - as in installations on cars, boats, or other vehicles; or in installations that might be installed or set up several times, such as portable shelving or displays.

- ✗ You have a large number of connections to make - particularly in installations that require many connections back to back, where one failure would result in the loss of large sections of light.
- ✗ You are installing in tight places - when the added size of the connector would make your LED strip installation difficult or impossible.
- ✗ Your connectors absolutely **MUST NOT** fail - as in connectors installed in hard to reach places, in products or installations you're delivering or shipping to a customer.

LEDtape Indoor Series IP00

KOPPLINGSDON MINI
CONNECTORS SLIM
VERBINDER KLEIN
CONNETTORI SOTTILE
CONECTORES DELGADO



STRIP TO CABLE

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the PCB.

3




Insert the LEDtape and cable all the way to the back of the connector. Make sure you **match the POLARITY** of the LEDtape with the cable.

4



Push firmly on the top of the connector until it locks in place. Use a pair of flat pliers if needed.


5



When pressed in place the top should be level with the rest of the connector to ensure a proper connection.

STRIP TO STRIP

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the PCB on both ends that you want to connect.

3



Insert the ends of the LEDtape all the way to the back of the connector. Make sure you **match the POLARITY** on both sides.

4



Push firmly on the top of the connector until it locks in place. Use a pair of flat pliers if needed.

5



When pressed in place the top should be level with the rest of the connector to ensure a proper connection.


If you are in doubt, consider soldering your connection instead. There is no substitute for a permanent soldered connection.

VIDEO TUTORIAL:



Do **NOT** use Quick Connectors when...

- ✗ You need to connect a pre-soldered joint.



- ✗ Your LED strips might be subjected to movement - as in installations on cars, boats, or other vehicles; or in installations that might be installed or set up several times, such as portable shelving or displays.

- ✗ You have a large number of connections to make - particularly in installations that require many connections back to back, where one failure would result in the loss of large sections of light.
- ✗ You are installing in tight places - when the added size of the connector would make your LED strip installation difficult or impossible.
- ✗ Your connectors absolutely **MUST NOT** fail - as in connectors installed in hard to reach places, in products or installations you're delivering or shipping to a customer.


LEDtape Outdoor Series IP68

INSTRUKTIONER
INSTRUCTIONS
ANLEITUNG
ISTRUZIONI
INSTRUCCIONES




INSTALLATION

1



Never bend the LEDtape at a radius smaller than 50 mm.

2




Assembly must not damage or destroy conducting paths on the PCB.

3

Perform the Pre-connection Checklist:


- ✓ Maximum length connected in series:
→ Datasheet | Wiring
- ✓ Polarity and Cable Colour Coding:
→ Datasheet | Wiring
- ✓ Maximum length per driver:
→ Datasheet | Digital Dimmable Drivers

4




The fixing/cooling surface must be properly cleaned to remove grease, dirt and silicon before application, e.g. using Isopropyl alcohol.

5



Remove the adhesive tape from the backside and fix the LEDtape on the cleaned fixing/cooling surface.


6



When fixing the LEDtape to a surface, apply an even but gentle pressure and try to avoid applying pressure directly on the LED itself (the maximum allowed pressure is 20 N/cm²).


After assembly always check that the entire length has attached properly to the surface and that there is no air pockets underneath.

7



If the total length is longer than 2 meters or when used in environments with large variations in temperature (e.g. outdoor applications) it is recommended to use the included screw mounting clips in addition to the adhesive tape.


8



Before you connect the power supply, make sure all cable connections have been properly sealed using weatherproof connectors, e.g. 3M Scotchlok (not included). Always use our approved drivers and controls to power the LEDtape. If the wrong type of driver is used the product warranty is void.







→ Datasheet | Digital Dimmable Drivers

9




The temperature on the surface of the LEDtape (t_c) may under no circumstances be higher than 65 °C if the expected lifetime of the LEDtape is to be met.

CUT & RE-SEAL




7




Thread the connection cable through the hole of the end cap.

8




Dispense a small portion of silicon inside the end cap and then slide it into place over the end of the LEDtape. Please wait 60 minutes for the silicone to solidify.

CUT IP68 = IP67



Do not place the re-sealed parts permanently under water! When cut and re-sealed properly the overall protection of the LEDtape will be reduced from IP68 to IP67.

SOLDERING



If you need to solder the LEDtape, pre-tin the cables only. Soldering temperature max 300 °C for 4 seconds.

For details on how to solder an IP68 LEDtape, please watch this VIDEO TUTORIAL:



LEDtape Outdoor Series IP68

KOPPLINGSDON
CONNECTORS
VERBINDER
CONNETTORI
CONECTORES




STRIP TO CABLE

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the LEDtape.

3




Position the connector sleeve to match the LEDtape with the hole facing upwards.

4




Use the included Silicon Tube to dispense silicon around the end of the LEDtape to facilitate the insertion into the connector sleeve.

5




Push the lubricated end of the LEDtape all the way into the sleeve.

6




Put the cable connector on top of the sleeve and push downwards. Make sure you **match the POLARITY** of the LEDtape with the connector before locking the connector in place.



Use a pair of flat pliers to press down on each side of the cap until they lock in position. A "CLICK" can be heard when the pins are locked.

LEDtape IP68 + Connectors = IP67



Do not use connectors permanently under water! When using connectors, the overall protection of the LEDtape will be reduced from IP68 to IP67.


STRIP TO STRIP

1




Cut the LEDtape in the middle of the solder pads.

2




Peel off approx. 1 cm of the adhesive tape from the back of the LEDtape.

3




Position the connector sleeves to match both ends of the LEDtape with the holes facing upwards.


4




Use the included Silicon Tube to dispense silicon around the ends of the LEDtape to facilitate the insertion into the connector sleeves.



Push the lubricated ends of the LEDtape all the way into the sleeves.




Put the bridge connector on top of the sleeves and push downwards. Make sure you **match the POLARITY** of the LEDtape with the connector before locking the bridge connector in place.



Use a pair of flat pliers to press down on each side of the cap until they lock in position. A "CLICK" can be heard when the pins are locked.


LEDtape IP68 + Connectors = IP67



Do not use connectors permanently under water! When using connectors, the overall protection of the LEDtape will be reduced from IP68 to IP67.

Do NOT use Quick Connectors when...

- × You need to connect a pre-soldered joint.



- × Your LED strips might be subjected to movement - as in installations on cars, boats, or other vehicles; or in installations that might be installed or set up several times, such as portable shelving or displays.

- × You have a large number of connections to make - particularly in installations that require many connections back to back, where one failure would result in the loss of large sections of light.
- × You are installing in tight places - when the added size of the connector would make your LED strip installation difficult or impossible.
- × Your connectors absolutely **MUST NOT** fail - as in connectors installed in hard to reach places, in products or installations you're delivering or shipping to a customer.

If you are in doubt, consider soldering your connection instead. There is no substitute for a permanent soldered connection.

VIDEO TUTORIAL:



SAFETY INSTRUCTIONS

- EN** Read these instructions carefully before starting the installation and save for future reference. All connections to the device must be made by a qualified electrician or person with the necessary expertise in electrical installation in accordance with relevant rules and standards. Make sure that the mains voltage is disconnected before installation or maintenance.
- SE** Läs dessa instruktioner innan installationen påbörjas och lämna dem vidare till brukaren av anläggningen. All anslutning till enheten får endast utföras av behörig elektriker eller person med kännedom om elektrisk installation i enlighet med gällande regler och standard. Se till att spänningen är frånslagen före installation eller underhåll.
- FI** Lue nämä ohjeet ennen asentamista ja luovuta ohjeet valaisimen seuraavalle käyttäjälle. Kytkenät ohjaimen saa tehdä ainoastaan pätevä sähköasentaja tai sähköasennukset hallitseva henkilö voimassa olevien määräysten ja standardien mukaisesti. Varmista, että jännite on kytketty päältä ennen asennusta ja huoltoa.
- NO** Les disse instruksjonene før du starter installeringen, og gi den deretter videre til anleggets bruker. All tilkobling til enheten skal utføres av godkjent elektriker eller person med nødvendig kunnskap om elektrisk installasjon i henhold til gjeldende forskrifter og standard. Sørg for at strømmen er koblet fra før installering og ved vedlikehold.
- DK** Læs disse anvisninger før du starter installationen og aflever vejledningen til anlæggets bruger. Alle tilslutninger på enheden skal udføres af en autoriseret elinstallatør i overensstemmelse med gældende regler og standarder. Afbryd spænding før installation og vedligeholdelse.